

## TECHNICAL DATA SHEET

**Item number:** 39214, 39216, 39218

**Item:** Facade plug

**Application:** It is used for fixing expanded polystyrene and basalt wool boards. It is used to attach insulation boards to the construction of an insulated building, under plaster. Depending on the type of insulation and the underlying structure, the correct type of plate dowel must be selected, which should be specified in the project documentation, as well as the number of dowels per m<sup>2</sup>.

Not suitable for wooden buildings.

### Advantages:

- High weather resistance
- No thermal bridge
- Easy installation

**Material:** Polypropylene

### Technical parameters:

Item number	Length (mm)	Recess length (mm)	Flange diameter (mm)	Wall drilling diameter (mm)	Fastener weight (g)	Nail weight (g)
39214	140	45	60	9,9	8,3	3,5
39216	160	45	60	9,9	8,7	3,9
39218	180	45	60	10	10,7	4,6

### The pulling force of the fastener:

Item number	Made of brick: (N)	Made of concrete: (N)	Made of AAC: (N)
39214	409	690	122
39216	376	749	98
39218	603	622	207

**Storage and Handling:** The products are packed in plastic bags, stored in dry rooms - inside the factory, protected from direct sunlight.

**Warranty:** In accordance with current legislation and distributor conditions, observance of the product application rules and presentation of the invoice is a prerequisite for possible future warranty claims.

